



PCB LAYOUT
<BOTTOM VIEW>

PART NO.	AJ2.5-151-A	AJ2.5-151-B	AJ2.5-151-C
SCHEMATIC			

- NOTES:**
- VOLTAGE AND CURRENT RATING: 16V DC, 0.3A.
 - WITHSTAND VOLTAGE: 250V AC FOR 1 MINUTE.
 - INSULATION RESISTANCE: 100M OHMS.
 - CONTACT RESISTANCE: 50m OHMS MAX.
 - OPERATING TEMPERATURE: -25°C TO +85°C.
 - RoHS COMPLIANT.

5	M5_GROUND CONTACT	BRASS	Ag 30u" OVER Ni 30u"
4	M4_TIP CONTACT	TiCu	Ag 30u" OVER Ni 30u"
3	M3_TIP SHUNT	BRASS	Ag 30u" OVER Ni 30u"
2	M1_RING CONTACT	PHOSPHOR BRONZE	Ag 30u" OVER Ni 30u"
1	HOUSING	LCP GF+30%, UL94V-0	BLACK
NO.	DESCRIPTION	MATERIAL	FINISHED

TOLERANCE	
LINEAR	ANGLES
X.±	X°±



TITLE: **Ø2.5mm EARPHONE JACK**

PART NO. AJ2.5-151-X

DWG NO. GT10-30144

ADD NOTES, DIM. BOM AND CORRECT TOLERANCE	AXL	12/01/10'	.X±0.38	.X°±	APPD:	MAT'L:	DWG NO.	GT10-30144		
ISSUED	JANE	06/28/06'	.XX±0.25	.XX°±	CHKD:	FINISH:	UNITS	SCALE	SHEET	REV
ECN NO.	NAME	DATE	.XXX±0.10	.XXX°±	DRWN:	Q'TY:	MM	NONE	1 OF 1	B