



ORDER INFORMATION

BH105-XX-XX

- └ PLATING
 - T1=TIN PLATING
 - F1=FULL GOLD FLASH
 - F2=5u" FULL GOLD
 - F3=10u" FULL GOLD
 - S1=SELECTIVE FLASH PLATING
 - S2=SELECTIVE 5u" PLATING
 - S3=SELECTIVE 10u" PLATING
- └ NO. OF POSITIONS
- └ TOOLING SERIES

NOTES:

- 1.CURRENT RATING:1AMP
- 2.INSULATOR RESISTANCE:5000 MEGAOHMS MIN.
- 3.DIELECTRIC WITHSTANDING: AC 500V.
- 4.OPERATING TEMPERATURE:-40°C~+105°C.
- 5.MATERIAL:
 - HOUSING:THERMOPLASTIC UL94V-0,BLACK.
 - TERMINAL:COPPER ALLOY.
- 6.RoHS COMPLIANT.

Dimension Information:

Part No.	Dim.	Pos.	Dim.A	Dim.B	Dim.C
BH105-10-XX	10		27.10	8.00	26.0
BH105-12-XX	12		29.10	10.00	28.0
BH105-14-XX	14		31.10	12.00	30.0
BH105-16-XX	16		33.10	14.00	32.0
BH105-20-XX	20		27.10	18.00	26.0
BH105-22-XX	22		29.10	20.00	28.0
BH105-24-XX	24		31.10	22.00	30.0
BH105-26-XX	26		33.10	24.00	32.0
BH105-30-XX	30		37.10	28.00	36.0
BH105-32-XX	32		39.10	30.00	38.0
BH105-34-XX	34		41.10	32.00	40.0
BH105-36-XX	36		43.10	34.00	42.0
BH105-40-XX	40		47.10	38.00	46.0
BH105-44-XX	44		51.10	42.00	50.0
BH105-50-XX	50		57.10	48.00	56.0
BH105-60-XX	60		67.10	58.00	66.0
BH105-64-XX	64		70.10	62.00	70.0
BH105-68-XX	68		75.10	66.00	74.0

Recommended P.C.B. Layout
Layout Tolerance = ± 0.05 mm

TOLERANCE	
LINEAR	ANGLES
X.±	X'±
.X±0.25	.X'±
.XX±0.15	.XX'±
.XXX±0.05	.XXX'±



TITLE: 2.0mm Pitch Box Header
R/A Type Dual Row

PART NO. BH105-XX-XX

DWG NO.

[A]	ISSUED	Bolin	11/15/06'
REV	ECN NO.	NAME	DATE

APPD:	MAT'L:
CHKD:	FINISH:
DRWN:	Q'TY:

UNITS	SCALE	SHEET	REV
MM	NONE	1 OF 1	A