



	PIN	TOLER.	PART NUMBER
	2.0	±0.15	DC211K-A
	2.5	±0.15	DC211K-B

NOTES:

1. RATING: DC 30V 2.0A
2. CONTACT RESISTANCE: 30mΩ MAX.
3. INSULATION RESISTANCE: 100MΩ MIN. (DC250V)
4. WITHSTAND VOLTAGE: 500VAC
5. INSERTION AND EXTRACTION FORCE: 3~20N
6. DURABILITY: 5000 CYCLES
7. RoHS COMPLIANT

TOLERANCE:

- 0.0 ≤ X < 10.0 ±0.10mm
- 10.0 ≤ X < 20.0 ±0.15mm
- 20.0 ≤ X < 50.0 ±0.20mm

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
6	PIN	1	BRASS	Ni 80u" MIN.
5	FLAT FOOT	1	BRASS	Ni+Sn 120u" MIN.
4	CURVE PIECE	1	BRASS	Ni+Sn 120u" MIN.
3	SPRING PIECE	1	BRONZE	Ni+Sn 120u" MIN.
2	COVER	1	PBT 4815BK	
1	HOUSING	1	PBT 4815BK	

				TOLERANCE		 <small>1015 GRANT STREET S.E. ATLANTA, GA 30315</small>		TITLE: DC JACK R/A THRU HOLE TYPE			
				LINEAR	ANGLES			PART NO. DC211K-X			
				X.±	X'±			DWG NO. GT11-20034			
[B]	UPDATED DRAWING	Jeff	01/25/11'	.X±0.30	.X'±	APPD:	MAT'L:	UNITS	SCALE	SHEET	REV
[A]	ISSUED	AXL	3/22/06'	.XX±0.20	.XX'±	CHKD:	FINISH:	MM	NONE	1 OF 1	B
REV	ECN NO.	NAME	DATE	.XXX±0.10	.XXX'±	DRWN: AXL	Q'TY:				