



- NOTES:
- MATERIALS:**  
 INSULATOR: GLASS FIBER REINFORCED THERMOPLASTIC PBT UL94V-0.  
 CONTACT: PHOSPHOR BRONZE, GOLD FLASH ON CONTACT, TIN PLATED ON TAIL 100u", OVER NICKEL PLATED 50u".  
 SHELL: STEEL, NICKEL PLATED.  
 BOARDLOCK: BRASS, TIN PLATED.  
 RIVET: BRASS, NICKEL PLATED.
  - ELECTRICAL:**  
 INSULATION RESISTANCE: 1000 MEGOHMS MINIMUM  
 DIELECTRIC WITHSTANDING VOLTAGE: 500V AC  
 VOLTAGE RATING: 40 VOLTS AC(RMS) MAXIMUM  
 CURRENT RATING: 3.0 AMPS PER CIRCUIT  
 CONTACT RESISTANCE: 20 MILLIOHMS MAXIMUM
  - MECHANICAL PERFORMANCE:**  
 MATING FORCES: 4.5kgf MAXIMUM  
 UNMATING FORCES: 1kgf MINIMUM, 4kgf MAXIMUM  
 DURABILITY: 100 CYCLES MINIMUM
  - ENVIRONMENTAL:**  
 TEMPERATURE RANGE: -20°C TO +85°C

\*RoHS Compliant \*

NO.	DESCRIPTION	Q'TY	MATERIAL
GENESIS TECHNOLOGIES 1015 GRANT STREET SE., ATLANTA, GA 30315			
圖名 NAME	DVI24+5 FEMALE CONN		
圖號 DWG NO	GT032-0302-5		
單位 UNIT	MM	一般公差	繪圖 DRAW. BY
比例 SCALE	none	.X _____	校對 CHECKED
SHEET	1/1	.XX _____	審核 APPVL. BY
		.XXX _____	
		ANGLES _____	

REV	DESCRIPTION	DATE	NAME	ECN NO.
A	ISSUED	9/28/05	AXL	