

NOTE:

- 1.MATERIAL:
 - a.HOUSING:LCP GLASS FIBRE UL94 V-0;BLACK
 - b.CONTACT:PHOSPHOR BRONZE T=0.25±0.02mm (SURFACE PLATING: Au1u"+Sn80u"+Ni60u")
 - c.SHEEL: BRONZE T=0.40±0.02mm (SURFACE PLATING: Ni100u")
- 2.ELECTRIC:
 - a.CONTACT RESISTANCE: 30 MILLIOHMS MAX
 - b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN
 - c.DIELECTNIC VOLTAGE: 500V AC ONE SEC LEVEL
 - d.OPERATING TEMPERATURE: -55°C~ 105°C
3. RoHS COMPLIANT.

ORDER INFORMATION

NUBR-22 05 - B K 1 3 T 1M

① ② ③ ④ ⑤ ⑥ ⑦

1. CONNECTOR:

NUBR: MINI USB B TYPE R/A CONNECTOR

2. TYPE:

22: SMT

3. POSITIONS

05: 5 POSTIONS

4. INSULATOR MATERIAL

B: LCP

5. INSULATOR COLOR


K: BLACK

6. CONTACT PLATING

1: GOLD 1u"

7. SHIELD PLATING

3: NICKEL PLATING

				TOLERANCE		 <small>7F, No. 191, Sec. 2 Chung-Yang Rd., Tu-Cheng City, Talpei Hsien, Taiwan</small> A Genesis Electro-Mechanical Company		MINI USB B TYPE SMT				
				LINEAR	ANGLES			PART NO.	NUBR-2205-BK13T1M			
				X. ±	X° ±4°			DWG NO.	GT109-25072			
[B]	UPDATE DIMENSIONS	Kevin	07/09/09	.X ±	.X° ±2°	APPD:	MAT'L:	UNITS	SCALE	SHEET	REV	
[A]	ISSUED	Vegas	06/17/09	.XX ±	.XX° ±2°	CHKD:	FINISH:	MM	NONE	1 OF 1	B	
REV.	ECN NO.	NAME	DATE	.XXX ±	.XXX° ±2°	DRWN: Vegas	Q'TY:					