



RECOMMENDED PCB LAYOUT
(TOL:±0.05)

NOTE:

- Electrical Characteristics:
Voltage Current rating:1AMP,30VAC
Insulation Resistance:100MΩ min
Contact Resistance:50MΩ max
- Environmental
Operating Temperature:-50°C to 85°C
- RoHS compliant.

ORDER INFORMATION

NUBR-23 05 - B X X 3 T 1C

① ② ③ ④ ⑤ ⑥ ⑦

- CONNECTOR:
NUBR: MINI USB B TYPE R/A CONNECTOR
- TYPE:
23: FEMALE, SMT
- POSITIONS
05: 5 POSTIONS
- INSULATOR MATERIAL
B: LCP
- INSULATOR COLOR
K: BLACK
W: WHITE
- CONTACT PLATING
1: GOLD 1u"
2: GOLD 3u"
3: GOLD 5u"
5: GOLD 15u"
6: GOLD 30u"
- SHIELD PLATING
3: NICKEL PLATING

TOLERANCE		GENESIS TECHNOLOGY, INC A Genesis Electro-Mechanical Company		MINI USB B TYPE SMT			
LINEAR	ANGLES			PART NO.	NUBR-2305-BXX3T1C		
X ±	X° ±3°	APPD:	MAT'L:	DWG NO.	GTI09-25073		
.X ± 0.38	.X° ±3°	CHKD:	FINISH:	UNITS	SCALE	SHEET	REV
.XX ± 0.25	.XX° ±3°	DRWN: Vegas	Q'TY:				

[A]	ISSUED	Vegas	06/17/09
REV.	ECN NO.	NAME	DATE