




**DETAIL Y**

MATERIAL: HOUSING-PBT POLYESTER UL-94V-0  
 MIXED GLASS FIBER.  
 STANDARD COLOR-BLACK  
 CONTACTS-0.35mm THICK PHOS-BRONZE  
 PLATED WITH HARD GOLD AND  
 TIN/LEAD IN SOLDER AREA.  
 SHIELD-0.25mm THICK COPPER ALLOY,  
 PLATED WITH NICKEL.  
 CAVITY CONFIRMS TO FCC RULES AND REGULATIONS  
 PART 68,SUBPART F.

**D ORDER INFORMATION**

RJ4R- 4J 16 - A K 1 3 T 1Q  
 ① ② ③ ④ ⑤ ⑥ ⑦

1. CONNECTOR:  
RJ4R: RJ45 R/A CONNECTOR
2. TYPE:  
4J: FEMALE, DIP TYPE, 2x1 8P RIGHT ANGLE SHIELDED PCB JACK
3. POSITIONS  
16: 16 POSTIONS
4. INSULATOR MATERIAL  
A: PBT
5. INSULATOR COLOR  
K: BLACK
6. CONTACT PLATING  
1: GOLD 1u"
7. SHIELD PLATING  
3: NICKEL PLATING

				TOLERANCE				TITLE: 2x1 8P RIGHT ANGLE SHIELDED PCB JACK				
				LINEAR	ANGLES			PART NO. RJ4R-4J16-AK13T1Q				
D	ADD Genesis Part Number	SWL	08/25/09			APPD:	MAT'L:	DWG NO. SC-10066				
C	ADD RoHS Compliant	AXL	8/8/06'	X.±	X'.±			CHKD:	FINISH:	 	UNITS	SCALE
B	SPECIFIED PIN POSITION	AXL	8/30/05'	.X±0.25	.X'±	DRWN: AXL	Q'TY:	MM	NONE		1 OF 1	D
A	ISSUED	AXL	8/23/05'	.XX±0.15	.XX'±							
REV	ECN NO.	NAME	DATE	.XXX±0.05	.XXX'±							

**C** \*RoHS COMPLIANT\*