



WIRE LIST

C1	COLOR	C2
1	RED	1
2	BLACK	2
3	BROWN	3
4	ORANGE	4
SHELL	D.W.	SHELL

NOTES:

- CABLE: [26AWG(7/0.16)x4C+AL/MY]TIN
INSULATION: SR-PVC, OD=ø1.0±0.05mm, COLOR: SEE WIRE LIST.
JACKET: 80°c PVC, OD=ø4.50±0.2mm, COLOR: BLACK, UL2464.
- TESTING:
(1) 100% TEST OPEN, SHORT AND MISWIRE.
(2) INSULATION RESISTANCE: 5 MEGAOHMS MIN.
(3) CONDUCTOR RESISTANCE: 3 OHMS MAX.
(4) HI-POT: 200V DC.
- RoHS COMPLIANT.
- Specify Length as Suffix on Part Number in mm.
For Example:
SVID-10442-1800 = 1800mm Long S-VIDEO Cable.

4	CABLE	1.8M	UL2464 26AWG*4C	
3	OVER-MOLD	25g	45P PVC BLACK	
2	PRE-MOLD	15g	PE	
1	4P MD PLUG	2PCS	PIN: TIN PLATED, SHELL: NI PLATED	
NO.	DESCRIPTION	Q'TY	MATERIAL	P/N

TOLERANCE	
LINEAR	ANGLES
X.±	X'±
.X±0.25	.X'±
.XX±0.15	.XX'±
.XXX±0.05	.XXX'±



TITLE:		4P MD S-VIDEO CABLE ASSY			
PART NO.		SVID-10442-X			
DWG NO.		SC-10442			
	UNITS	SCALE	SHEET	REV	
	MM	NONE	1 OF 1	A	

[A]	ISSUED	AXL	1/3/07'
REV	ECN NO.	NAME	DATE