






**NOTES:**

1. Electrical Characteristics:  
 Contact Current Rating: 1.5 Amperes.  
 Dielectric Withstanding Voltage: AC 500V R.M.S.  
 Insulation Resistance: 1000M $\Omega$  Min.  
 Contact Resistance: 30m $\Omega$  Max .
2. Environmental :  
 Operating Temperature :-30°C to +85°C.
3. Mechanical Characteristics:  
 Mating Force: 3.57kg Max.  
 Unmating Force: 1.02kg Min.
4. Material:  
 Housing: PBT UL 94V-0 Rated.  
 Contacts: Copper Alloy (t=0.25mm).  
 Shell: Steel (t=0.30mm). Nickel plated.
5. RoHS Compliant

**ORDER INFORMATION**

**USAR- 11 04 - A X X 3 T 1**  
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧

1. CONNECTOR:  
 USAR: USB A TYPE R/A CONNECTOR
2. TYPE:  
 11: MALE, DIP, WITH  $\phi$ 1.00 BOSS
3. POSITIONS  
 04: 4 POSITIONS
4. INSULATOR MATERIAL  
 A: PBT
5. INSULATOR COLOR  
 K: BLACK  
 W: WHITE
6. CONTACT PLATING  
 1: GOLD FLASH  
 2: GOLD 3 u"  
 3: GOLD 5 u"  
 5: GOLD 15 u"  
 6: GOLD 30 u"
7. SHIELD PLATING  
 3: NICKEL PLATED

TOLERANCE		 <small>7F, No. 191, Sec. 2          Chung-Yang Rd.,          Tu-Cheng City          Taipei Hsien, Taiwan</small>	TITLE:				
LINEAR	ANGLES		USB A MALE DIP TYPE WITH BOSS				
X. $\pm$	X $^{\circ}$ $\pm$ 3 $^{\circ}$	APPD:	MAT'L:	PART NO.		USAR-1104-AXX3T1	
.X $\pm$ 0.38	.X $^{\circ}$ $\pm$ 3 $^{\circ}$			DWG NO.		GTI08-25111	
.XX $\pm$ 0.25	.XX $^{\circ}$ $\pm$ 3 $^{\circ}$	CHKD:	FINISH:	 UNITS	 SCALE	 SHEET	 REV
.XXX $\pm$ 0.10	.XXX $^{\circ}$ $\pm$ 3 $^{\circ}$	DRWN: Kathy-Tan	Q'TY:				

A	ISSUED	Vegas	10/23/08'
REV.	ECN NO.	NAME	DATE