

NOTES:

*Electrical Characteristics:
 Contact Current Rating:1.5Amperes.
 Dielectric Withstanding Voltage:AC 500V R.M.S.
 Insulation Resistance:1000MΩ Min.
 Contact Resistance:30mΩ Max.

*Environmental:
 Operating Temperature:−30°C~+85°C.

*Mechanical Characteristics:
 Mating Force:3.57kg Max.
 Unmating Force:1.02kg Min.

* Materials:
 Housing: See "Order information" , UL 94V-0 Rated.
 Contacts: Copper Alloy(t=0.25mm).
 Shell: Cold Rolled Steel(t=0.30mm).
 There should not be any circuitries in the layout space of the PCB type products.


* RoHS Compliant

ORDER INFORMATION

USAR- 14 04 - X X X 3 T 1

- ① ② ③ ④ ⑤ ⑥ ⑦

1. CONNECTOR:
USAR: USB A TYPE R/A CONNECTOR
2. TYPE:
14: MALE, DIP TYPE, 1.0mm, WITH BOSS
3. POSITIONS
04: 4 POSITIONS
- B** 4. INSULATOR MATERIAL
B: LCP
F: NYLON9T
5. INSULATOR COLOR
K: BLACK
W: WHITIE
6. CONTACT PLATING
1: GOLD FLASH
2: GOLD 3 u"
3: GOLD 5 u"
5: GOLD 15 u"
6: GOLD 30 u"
7. SHIELD PLATING
3: NICKEL PLATED

				TOLERANCE		 <small>7F, No. 191, Sec. 2 Chung-Yang Rd., Tu-Cheng City Talpei Hsien, Taiwan</small>		TITLE: USB A MALE DIP 1.0mm WITH BOSS			
		LINEAR	ANGLES	PART NO.				USAR-1404-XXX3T1			
		X. ±	X° ±3°	DWG NO.				GTI08-25114			
B	ADD MATERIAL OPTION	Vegas	10/31/08'	.X ± 0.38	.X° ±3°	APPD:	MAT'L:	UNITS	SCALE	SHEET	REV
A	ISSUED	Vegas	10/24/08'	.XX ± 0.25	.XX° ±3°	CHKD:	FINISH:	mm	NONE	1 OF 1	B
REV.	ECN NO.	NAME	DATE	.XXX ± 0.10	.XXX° ±3°	DRWN: Kathy-Tan	Q'TY:				